

# GRM Process

GRM Pellet is composed of wood powder from virgin spruce tree, resin and additive, the powder are mixed to a dough-like consistency and then extruded out to form GRM Pellet.

## PRODUCTION PROCESS

### STAGE 1

Wood Powder Raw Materials



#### Mixer

Raw materials are placed into the mixer and mixed evenly.

### STAGE 2



#### Pelletizer

Pellets are then extruded out from the pelletizer at a formulated temperature.

### FINAL STAGE



#### Package and Deliver

The pellets are then finally packaged and delivered.

# Products



Cedar



Teak



Grey



Deep Walnut



Pine Wood



Mahogany



Red Cedar



Weather Wood

# Surface Finish Appearance



Original



Linish



Embossed



Sanding



Sanding Embossed



Flooring



Decking



Ceiling



Wall Panel



Facade Screen



Louver Blades



Car Porch



Gate



Fence

## GRM Green Products (M) Sdn Bhd

No.3, Jalan Dataran 5, Taman Kempas 81200, Johor Bahru, Johor, Malaysia.

Tel : 07- 232 6407

Fax : 07- 232 3514

## Green Biowood (S) Pte Ltd

27, Tech Park Crescent, Singapore 638105

Tel : (+65) 6752 1954

Fax : (+65) 6752 6316

E Mail: info@greenstarproducts.com.sg